

A close-up, grayscale photograph of a Parker GlobalCore hose and fitting system. The hose is the central focus, with several fittings attached. The Parker logo and 'GLOBALCORE' are visible on the hose. The background is dark and out of focus.

ANY PRESSURE.
ANY PROJECT.
ONE SOLUTION.

GLOBALCORE™

The world's first high-performance,
cohesive hose and fitting system.



ENGINEERING **YOUR** SUCCESS.

PROVEN PERFORMANCE. GLOBAL SOLUTION.



Providing one simple solution of robust hydraulic hoses designed to endure the tough conditions where work gets done, **GlobalCore** is the future that OEMs and end users around the world have been asking for.



HIGH PERFORMANCE

With GlobalCore hoses tested to twice their ISO 18752 standard, high performance in rugged environments and high impulse applications is ensured.



COHESIVE

GlobalCore is a unified system that delivers hoses designed, engineered, and manufactured to the global specification, ISO 18752, which is based on performance and pressure requirements.



GLOBAL

GlobalCore hoses are manufactured in major regions of the world, supporting the equipment they serve, regardless of where it was originally manufactured, or where it is today.



SIMPLE

Select the GlobalCore hose based on the working pressure required for your application and one of two fitting series in a wide array of configurations.




For the latest list of hose and agency approvals, visit parkerglobalcore.com.

187 HOSE

MEETING THE DEMANDS OF COMPLEX HYDRAULIC SYSTEMS AND HIGH PRESSURE RETURN LINES

Designed, build and tested to the ISO 18752 performance specifications. For high pressure return line applications in all markets.



Part Number	Cover Type			Hose I.D.				Hose O.D. mm	Pressure Rating				Vacuum* kPa	min. bend radius mm	weight kg
	Standard Cover 187	Tough Cover 187TC	Super Tough 187ST	DN	Inch	Size	mm		max. working pressure		min. burst pressure				
	ISO 18752 Performance								MPa	psi	MPa	psi			
187XX-8	AC	AC	AC	12	1/2	-8	12.7	21.0	7.0	1000	28.0	4000	80	65	0.43
187XX-10	AC	AC	AC	16	5/8	-10	15.9	24.0	7.0	1000	28.0	4000	80	75	0.49
187XX-12	AC	AC	AC	19	3/4	-12	19.1	27.0	7.0	1000	28.0	4000	80	90	0.63
187XX-16	AC	AC	AC	25	1	-16	25.4	36.0	7.0	1000	28.0	4000	80	114	0.91
187XX-20	AC	AC	AC	31	1 1/4	-20	31.8	44.0	7.0	1000	28.0	4000	60	140	1.85
187XX-24	AC	AC	AC	38	1 1/2	-24	38.1	52.0	7.0	1000	28.0	4000	60	248	1.96
187XX-32	AC	AC	AC	51	1	-32	50.8	65.0	7.0	1000	28.0	4000	60	318	2.60
187XX-40	AS	AS	AS	63	2 1/2	-40	63.5	75.0	7.0	1000	28.0	4000	60	508	3.04
187XX-48	AS	AS	AS	76	3	-48	76.2	91.0	7.0	1000	28.0	4000	60	508	4.12

Inner Tube: Synthetic Rubber

Reinforcement: One- or two-braid steel wire

Temperature Range: Standard Cover: -40°C to +100°C,
ToughCover & SuperTough: -40°C to +125°C
For -40 & -48 sizes only -40°C to +100°C

Fitting Series:

Series 43/48 for sizes -8 to -32

Series 48 2piece for sizes -40 to -48



387 HOSE

DELIVERING VALUE AND PERFORMANCE FOR HIGH-PRESSURE APPLICATIONS

Lightweight and flexible, 387 Hose consistently delivers maximum performance and hose life across all sizes and markets using an efficient force-to-flex design.



Part Number	Cover Type			Hose I.D.				Hose O.D. mm	Pressure Rating				min. bend radius mm	weight kg
	Standard Cover 387	Tough Cover 387TC	Super Tough 387ST	DN	Inch	Size	mm		max. working pressure		min. burst pressure			
	ISO 18752 Performance								MPa	psi	MPa	psi		
387XX-4	AC	AC	AC	6	1/4	-4	6.4	13.4	21.0	3000	84.0	12000	50	0.24
387XX-6	AC	AC	AC	10	3/8	-6	9.5	17.4	21.0	3000	84.0	12000	65	0.34
387XX-8	AC	AC	AC	12	1/2	-8	12.7	20.7	21.0	3000	84.0	12000	90	0.43
387XX-10	AC	AC	AC	16	5/8	-10	15.9	23.9	21.0	3000	84.0	12000	100	0.49
387XX-12	AC	AC	AC	19	3/4	-12	19.1	27.8	21.0	3000	84.0	12000	120	0.86
387XX-16	AC	AC	AC	25	1	-16	25.4	35.4	21.0	3000	84.0	12000	150	1.17
387XX-20	BC	CC	CC	31	1 1/4	-20	31.8	46.3	21.0	3000	84.0	12000	210	2.59
387XX-24	BC	CC	CC	38	1 1/2	-24	38.1	52.8	21.0	3000	84.0	12000	250	2.99
387XX-32	BC	CC	CC	51	2	-32	50.8	66.2	21.0	3000	84.0	12000	320	4.09

Inner Tube: Synthetic Rubber

Reinforcement: One- or two-braid steel wire for sizes -4 to -16
Four-spiral for sizes -20 to -32


Temperature Range: Standard Cover: -40°C to +100°C
ToughCover & SuperTough: -40°C to +125°C

Fitting Series:

Series 43/48 for sizes -4 to -16

Series 43/77 for size -20

Series 77 for sizes -24 to -32



487 HOSE

HIGHLY FLEXIBLE ACROSS ALL SIZES

Constructed for high performance and easy handling with low force-to-flex for ease of installation, 487 Hose excels in multiple applications around the world.



Part Number	ISO 18752 Performance			Hose I.D.				Hose O.D. mm	Pressure Rating				min. bend radius mm	weight kg
	Standard Cover 487	Tough Cover 487TC	Super Tough 487ST	DN	Inch	Size	mm		max. working pressure		min. burst pressure			
	MPa	psi	MPa	psi	MPa	psi	MPa	psi	MPa	psi				
487XX-4	AC	AC	AC	6	1/4	-4	6.4	13.1	28.0	4000	112.0	16000	50	0.30
487XX-6	AC	AC	AC	10	3/8	-6	9.5	17.2	28.0	4000	112.0	16000	65	0.42
487XX-8	AC	AC	AC	12	1/2	-8	12.7	20.4	28.0	4000	112.0	16000	90	0.52
487XX-10	AC	AC	AC	16	5/8	-10	15.9	23.9	28.0	4000	112.0	16000	100	0.66
487XX-12	AC	AC	AC	19	3/4	-12	19.1	27.8	28.0	4000	112.0	16000	120	0.86
487XX-16	BC	CC	CC	25	1	-16	25.4	37.8	28.0	4000	112.0	16000	150	1.99
487XX-20	BC	CC	CC	31	1 1/4	-20	31.8	46.3	28.0	4000	112.0	16000	210	2.59
487XX-24	BC	CC	CC	38	1 1/2	-24	38.1	52.8	28.0	4000	112.0	16000	250	3.08
487XX-32	BC	CC	-	51	2	-32	50.8	64.8	28.0	4000	112.0	16000	320	4.09

Inner Tube: Synthetic Rubber

Reinforcement: One- or two-braid steel wire for sizes -4 to -12

Four-spiral wires for sizes -16 to -24 | Six-spiral wires for size -32

Temperature Range: Standard Cover: -40°C to +100°C


ToughCover & SuperTough: -40°C to +125°C

Fitting Series:

Series 43/48 for sizes -4 to -12

Series 43 for size -16


Series 77 for sizes -20 to -32



722 HOSE

RESILIENT 4-WIRE SPIRAL CONSTRUCTION

Engineered to ensure longer life in high-impulse, heavy-duty cycle applications, 722 Hose delivers maximum performance and efficiency.



Part Number	ISO 18752 Performance			Hose I.D.				Hose O.D. mm	Pressure Rating				min. bend radius mm	weight kg
	Standard Cover 722	Tough Cover 722TC	Super Tough 722ST	DN	Inch	Size	mm		max. working pressure		min. burst pressure			
	MPa	psi	MPa	psi	MPa	psi	MPa	psi	MPa	psi				
722XX-6	BC	CC	CC	10	3/8	-6	9.5	19.9	28.0	4000	112.0	16000	65	0.60
722XX-8	BC	CC	CC	12	1/2	-8	12.7	22.7	28.0	4000	112.0	16000	90	0.80
722XX-10	BC	CC	CC	16	5/8	-10	15.9	26.4	28.0	4000	112.0	16000	100	1.10
722XX-12	BC	CC	CC	19	3/4	-12	19.1	30.7	28.0	4000	112.0	16000	120	1.40
722XX-16	BC	CC	CC	25	1	-16	25.4	37.8	28.0	4000	112.0	16000	150	1.99

Inner Tube: Synthetic Rubber

Reinforcement: Four-spiral steel wire

Temperature Range: Standard Cover: -40°C to +100°C

ToughCover & SuperTough: -40°C to +125°C

Fitting Series:

Series 43



787 HOSE

LIGHTER WEIGHT, HIGHER FLEXIBILITY, TIGHTER BEND RADIUS

With a Compact Spiral design that offers enhanced chemical compatibility in routing and installation, 787 Hose delivers superior performance in a lightweight, force-to-flex product.



Part Number	ISO 18752 Performance			Hose I.D.				Hose O.D. mm	Pressure Rating				min. bend radius mm	weight kg
	Standard Cover 787	Tough Cover 787TC	Super Tough 787ST	DN	Inch	Size	mm		max. working pressure		min. burst pressure			
								MPa	psi	MPa	psi			
787XX-4	AC	AC	AC	6	1/4	-4	6.3	13.0	35.0	5000	140.0	20000	50	0.31
787XX-6	AC	AC	AC	10	3/8	-6	10.0	17.2	35.0	5000	140.0	20000	63	0.42
787XX-8	BC	DC	DC	12	1/2	-8	12.7	21.1	35.0	5000	140.0	20000	90	0.67
787XX-10	BC	DC	DC	16	5/8	-10	15.9	23.9	35.0	5000	140.0	20000	100	0.80
787XX-12	BC	DC	DC	19	3/4	-12	19.1	27.9	35.0	5000	140.0	20000	120	1.16
787XX-16	BC	DC	DC	25	1	-16	25.4	35.7	35.0	5000	140.0	20000	150	1.74
787XX-20	BC	DC	DC	31	1 1/4	-20	31.8	44.9	35.0	5000	140.0	20000	210	2.89
787XX-24	BC	DC	DC	38	1 1/2	-24	38.1	52.8	35.0	5000	140.0	20000	255	3.96
787XX-32	BC	DC	DC	51	2	-32	50.8	67.6	35.0	5000	140.0	20000	318	6.50

Inner Tube: Synthetic Rubber

Reinforcement: Two-braid steel wire for sizes -4 to -6

Four- or six-compact spiral steel wires for sizes -8 to -32

Temperature Range: Standard Cover: -40°C to +100°C

ToughCover & SuperTough: -40°C to +125°C (-4 to -6 rated to +100°C)

Fitting Series:

Series 43/48 for sizes -4 and -6

Series 77 for sizes -8 to -32



35 MPa (5000 psi)

797 HOSE

COMPACT DESIGN FOR TIGHTER ROUTING AND SPACE SAVINGS

Tested up to 2,000,000 cycles, 797 Hose provides enhanced chemical compatibility and service life with an easy-to-install compact spiral construction for high pressure, high impulse applications.



Part Number	ISO 18752 Performance			Hose I.D.				Hose O.D. mm	Pressure Rating				min. bend radius mm	weight kg
	Standard Cover 797	Tough Cover 797TC	Super Tough 797ST	DN	Inch	Size	mm		max. working pressure		min. burst pressure			
								MPa	psi	MPa	psi			
797XX-4	AC	AC	AC	6	1/4	-4	6.3	13.0	42.0	6000	168.0	24000	50	0.31
797XX-6	BC	CC	CC	10	3/8	-6	10.0	17.0	42.0	6000	168.0	24000	63	0.46
797XX-8	BC	DC	DC	12	1/2	-8	12.7	21.1	42.0	6000	168.0	24000	100	0.67
797XX-10	BC	DC	DC	16	5/8	-10	15.9	23.9	42.0	6000	168.0	24000	115	0.80
797XX-12	BC	DC	DC	19	3/4	-12	19.1	27.9	42.0	6000	168.0	24000	135	1.16
797XX-16	BC	DC	DC	25	1	-16	25.4	35.7	42.0	6000	168.0	24000	165	1.74
797XX-20	BC	DC	DC	31	1 1/4	-20	31.8	44.9	42.0	6000	168.0	24000	225	2.89
797XX-24	BC	CC	CC	38	1 1/2	-24	38.1	52.8	42.0	6000	168.0	24000	305	3.96
797XX-32	BC	CC	CC	51	2	-32	50.8	67.6	42.0	6000	168.0	24000	380	6.50

Inner Tube: Synthetic Rubber

Reinforcement: Two-braid steel wire for size -4

Four- or six-compact spiral steel wires for sizes -6 to -32

Temperature Range: Standard Cover: -40°C to +100°C

ToughCover & SuperTough: -40°C to +125°C (-4 rated to +100°C)

Fitting Series:

Series 43/48 for sizes -4

Series 43 for size -6

Series 77 for sizes -8 to -32



42 MPa (6000 psi)

Parker Worldwide

Europe, Middle East, Africa

AE – United Arab Emirates,
Dubai

Tel: +971 4 8127100
parker.me@parker.com

AT – Austria, St. Florian

Tel: +43 (0)7224 66201
parker.austria@parker.com

AZ – Azerbaijan, Baku

Tel: +994 50 2233 458
parker.azerbaijan@parker.com

BE/NL/LU – Benelux,

Hendrik Ido Ambacht
Tel: +31 (0)541 585 000
parker.nl@parker.com

BG – Bulgaria, Sofia

Tel: +359 2 980 1344
parker.bulgaria@parker.com

BY – Belarus, Minsk

Tel: +48 (0)22 573 24 00
parker.poland@parker.com

CH – Switzerland, Etoy

Tel: +41 (0)21 821 87 00
parker.switzerland@parker.com

CZ – Czech Republic, Klecany

Tel: +420 284 083 111
parker.czechrepublic@parker.com

DE – Germany, Kaarst

Tel: +49 (0)2131 4016 0
parker.germany@parker.com

DK – Denmark, Ballerup

Tel: +45 43 56 04 00
parker.denmark@parker.com

ES – Spain, Madrid

Tel: +34 902 330 001
parker.spain@parker.com

FI – Finland, Vantaa

Tel: +358 (0)20 753 2500
parker.finland@parker.com

FR – France, Contamine s/Arve

Tel: +33 (0)4 50 25 80 25
parker.france@parker.com

GR – Greece, Piraeus

Tel: +30 210 933 6450
parker.greece@parker.com

HU – Hungary, Budaörs

Tel: +36 23 885 470
parker.hungary@parker.com

IE – Ireland, Dublin

Tel: +353 (0)1 466 6370
parker.ireland@parker.com

IL – Israel

Tel: +39 02 45 19 21
parker.israel@parker.com

IT – Italy, Corsico (MI)

Tel: +39 02 45 19 21
parker.italy@parker.com

KZ – Kazakhstan, Almaty

Tel: +7 7273 561 000
parker.easteurope@parker.com

NO – Norway, Asker

Tel: +47 66 75 34 00
parker.norway@parker.com

PL – Poland, Warsaw

Tel: +48 (0)22 573 24 00
parker.poland@parker.com

PT – Portugal

Tel: +351 22 999 7360
parker.portugal@parker.com

RO – Romania, Bucharest

Tel: +40 21 252 1382
parker.romania@parker.com

RU – Russia, Moscow

Tel: +7 495 645-2156
parker.russia@parker.com

SE – Sweden, Spånga

Tel: +46 (0)8 59 79 50 00
parker.sweden@parker.com

SK – Slovakia, Banská Bystrica

Tel: +421 484 162 252
parker.slovakia@parker.com

SL – Slovenia, Novo Mesto

Tel: +386 7 337 6650
parker.slovenia@parker.com

TR – Turkey, Istanbul

Tel: +90 216 4997081
parker.turkey@parker.com

UA – Ukraine, Kiev

Tel: +48 (0)22 573 24 00
parker.poland@parker.com

UK – United Kingdom, Warwick

Tel: +44 (0)1926 317 878
parker.uk@parker.com

ZA – South Africa, Kempton Park

Tel: +27 (0)11 961 0700
parker.southafrica@parker.com

North America

CA – Canada, Milton, Ontario

Tel: +1 905 693 3000

US – USA, Cleveland

Tel: +1 216 896 3000

Asia Pacific

AU – Australia, Castle Hill

Tel: +61 (0)2-9634 7777

CN – China, Shanghai

Tel: +86 21 2899 5000

HK – Hong Kong

Tel: +852 2428 8008

IN – India, Mumbai

Tel: +91 22 6513 7081-85

JP – Japan, Tokyo

Tel: +81 (0)3 6408 3901

KR – South Korea, Seoul

Tel: +82 2 559 0400

MY – Malaysia, Shah Alam

Tel: +60 3 7849 0800

NZ – New Zealand, Mt Wellington

Tel: +64 9 574 1744

SG – Singapore

Tel: +65 6887 6300

TH – Thailand, Bangkok

Tel: +662 186 7000

TW – Taiwan, Taipei

Tel: +886 2 2298 8987

South America

AR – Argentina, Buenos Aires

Tel: +54 3327 44 4129

BR – Brazil, Sao Jose dos Campos

Tel: +55 800 727 5374

CL – Chile, Santiago

Tel: +56 2 623 1216

MX – Mexico, Toluca

Tel: +52 72 2275 4200

EMEA Product Information Centre

Free phone: 00 800 27 27 5374

(from AT, BE, CH, CZ, DE, DK, EE, ES, FI, FR, IE, IL,
IS, IT, LU, MT, NL, NO, PL, PT, RU, SE, SK, UK, ZA)

US Product Information Centre

Toll-free number: 1-800-27 27 537

www.parker.com

