


drain connection ($P_{\text{drain}} < 0,5 \text{ bar}$)
(Always connect directly to the tank)

Symbol



Type for 4xØ11:
30MR...X568HG(M)F

Type	Displacement	Pressure	Speed	Dimensions					
				A	B	Inlet		Outlet	
						M	G	M	G
	cm ³	Pmax, [bar	n [min ⁻¹]	mm		mm	”	mm	”
30MR22.5X568HG(M)	22.5	200	500 ... 2500	57.6	119.7	M27x1.5	G3/4—A	M27x1.5	G3/4—A
30MR25X568HG(M)	25	200	500 ... 2500	58.3	121.1	M27x1.5	G3/4—A	M27x1.5	G3/4—A
30MR28X568HG(M)	28	200	500 ... 2500	60.2	124.7	M27x1.5	G3/4—A	M27x1.5	G3/4—A
30MR32X568HG(M)	32	200	500 ... 2500	66.5	137.3	M33x1.5	G1—A	M33x1.5	G1—A
30MR36X568HG(M)	36	200	500 ... 2300	68	140.5	M33x1.5	G1—A	M33x1.5	G1—A
30MR42X568HG(M)	42	200	500 ... 2300	70.8	146.1	M33x1.5	G1—A	M33x1.5	G1—A
30MR46X568HG(M)	46	200	500 ... 2100	72.7	149.8	M33x1.5	G1—A	M33x1.5	G1—A
30MR50X568HG(M)	50	200	500 ... 2100	74.5	153.4	M33x1.5	G1—A	M33x1.5	G1—A
30MR55X568HG(M)	55	200	500 ... 1750	76.7	157.9	M33x1.5	G1—A	M33x1.5	G1—A
30MR60X568HG(M)	60	180	500 ... 1750	78.7	162.4	M33x1.5	G1—A	M33x1.5	G1—A